

Our sealers and how they compare:

	COLORFRESH® intensiv protective coating	COLORFRESH® effect protective coating	COLORTEC® MAX protective coating	COLORTEC® finish protective coating	PROWALL II anti-graffiti-coating and stain blocker
Areas of application:					
floors/paving	✓	✓	✓	✓	-
walls/facades	✓	✓	✓	✓	✓
decoration and design	✓	✓	✓	✓	✓
indoors	✓	✓	✓	✓	✓
outdoors	✓	✓	✓	✓	✓
Suitable for following types of concrete:					
prefabricated (precast) elements	✓	✓	✓	✓	✓
ready mixed concrete (cast-in-place)	✓	0	0	✓	✓
wetcast and self-compacting (self-levelling) concrete	✓	✓	✓	✓	✓
dry-cast concrete (pavers, blocks, bricks, slabs, tiles)	✓	✓	✓	✓	✓
glassfibre reinforced concrete (GFRC)	✓	✓	✓	✓	✓
concrete used for city furniture and landscaping	✓	✓	✓	✓	✓
terrazzo and decorative concrete floors and pavings	✓	✓	✓	✓	0
DIY concrete, cement & gipsum based crafts	✓	✓	✓	✓	✓
Suitable for following types of surface:					
smooth, form-finish or formliner-structured	✓	0	0	✓	✓
acid-etched	✓	✓	✓	✓	✓
sand-blasted / shot-blasted	✓	✓	✓	✓	✓
exposed-aggregate	✓	✓	✓	✓	✓
bush-hammered	✓	✓	✓	✓	✓
polished / ground / honed	✓	✓	✓	✓	✓
Product characteristics:					
matt (invisible) finish	✓	✓	✓	✓	✓
colour-enhancing	✓	√√	-	-	-
creates a silky sheen	✓	-	-	-	-
water-based / solvent-free	√	✓	√	✓	✓
breathable / permits water vapour diffusion	✓	✓	✓	✓	0
water-repellent / hydrophobic	✓	✓	✓	✓	✓
dirt-repellent	√√	✓	✓	✓	√√
oil-repellent / oleophobic	✓	✓	✓	-	✓
uv-resistant	✓	✓	✓	✓	✓
free of SVHCs and free of microplastics	✓	✓	✓	✓	✓
free of PFAS	✓	✓	-	✓	✓
free of PFOA/PFOS	✓	✓	✓	✓	✓
tested an approved as safe for contact with food	✓	not yet tested	✓	✓	✓
thermal stability	around +150°C	around +150°C	not yet evaluated	around +350°C	at least +60°C
applicable on dry surfaces	✓	✓	✓	✓	✓
applicable on moist surfaces	✓	✓	✓	✓	-
Protects against:					
efflorescence	✓	✓	✓	✓	-
freeze- / thaw damage	✓	✓	✓	✓	✓
food stains	✓	✓	✓	0	✓
general soiling	✓	✓	✓	✓	✓
growth of moss and algae	✓	✓	✓	✓	✓
weathering, damage, fading of colours	✓	✓	✓	✓	✓
graffiti	-	-	0	-	✓